

**SECTION I-MATERIAL IDENTIFICATION AND USE**

Material Name/Identifier:	Semi Flat Black super enamel	Stock No.	4503
Manufacturer's Name:	Kleen-Flo Tumbler Industries Ltd	Street Address:	75 Advance Blvd.
City:	Brampton	Province:	Ontario
Postal Code:	L6T 4N1	Emergency Phone #:	CANUTEC:- 613-996-6666 (24HR)
Chemical Name:	N/A (mixture)	Chemical Family:	Modified resin solution
Chemical Formula:	N/A (mixture)	Trade Names & Synonyms:	None
Material Use:	Aerosolized Paint	Molecular Weight:	N/A (mixture)

**SECTION II-HAZARDOUS INGREDIENTS OF MATERIAL**

Hazardous Ingredients	C.A.S.	Approximate %Concentration	LD50 Species & Route	LC50 Species & Route
Xylene	1330-20-7	1-5	4300 mg/kg rat-oral	6350 ppm (4hr) rat-oral
Acetone	67-64-1	30-60	>9750 mg/kg rat-oral	>16000 ppm (4hr) rat-inh.
Toluene	108-88-3	5-10	5000mg/kg rat-oral	8000 ppm(4hr) rat-inh.
Propylene Glycol Methyl Ether Acetate	108-65-6	1-5	8500mg/kg rat-oral	>4345 ppm(6hr) rat-inh.
n-Butyl Acetate	123-86-4	1-5	13100 mg/kg rat-oral	2000 ppm (4hr) rat-inh.
n-Butyl Alcohol	71-36-3	1-5	790-4360mg/kg rat-oral	8000 ppm(4hr) rat-inh.
Ethyl Acetate	141-78-6	1-5	6100 mg/kg rat-oral	2263 ppm (4hr) rat-inh.
Propylene Glycol Methyl Ether	107-98-2	1-5	5660 mg/kg rat-oral	7000 ppm(4hr) rat-inh.
Propane	74-98-6	7-13	>5000 mg/kg rabbits-Dermal	N/Av.
Carbon black	1333-86-4	0.1-1.0	>10000mg/kg rat-oral	N/Av.
Isobutane	75-28-5	5-10	N/Ap	142,500 ppm(4 hr), rat-inhl.

**SECTION III-PHYSICAL DATA FOR MATERIAL**

Physical State:	Aerosol	Odour/Appearance:	Ketone odour/ black liquid
Specific Gravity:	0.87-0.91	Odour Threshold(p.p.m.):	N/Av.
Boiling Point:	57 to 150°C	Evaporation Rate:	>1
Freezing Point:	N/Av.	Solubility in Water:	N/Av.
% Volatile(by volume):	88-89	Vapour Pressure	55-65 psig
Vapour Density(Air=1):	> 1	Coefficient of Water/Oil Distribut:	N/Av.

**SECTION IV-FIRE AND EXPLOSION HAZARD OF MATERIAL**

Flammability Yes/No	Yes	If yes under which conditions?: Excessive heat, open flame or sparks	
Auto Ignition Temperature:	272-527°C	Means of Extinction: Water, Carbon dioxide, dry chemical, foam	
Flashpoint and Method:	> -18°C	Tag. C.C	Hazardous Combustion Products: Hydrocarbon fumes &
Aerosol Flame Projection	> 15 cm But < 100 cm	smoke. Carbon monoxide where combustion is incomplete.	
Upper Flammable limit%vol	15.1	Lower Flammable Limit (% by volume):	1.p
Explosion Data:	Sensitivity to Mechanical Impact: N.Ap.	Sensitivity to Static Discharge:	N.Ap.

**SECTION V-REACTIVITY DATA**

Chemical Stability Yes/No:	Yes	If NO under which conditions?	N.Ap.
Incompatibility to Other Substances Yes/No:	Yes	If so which ones?	Strong oxidzers
Reactivity and under what conditions?	N/E		
Hazardous Decomposition Products:	Hydrocarbon fumes & smoke. Carbon monoxide where combustion is incomplete.		

**SECTION VI-TOXICOLOGICAL PROPERTIES OF PRODUCT**

Route of Entry: ALL Routes --SKIN CONTACT --SKIN ABSORPTION --EYE CONTACT --INHALATION --INGESTION

Effects of Acute Exposure: Dizziness and nausea. Irritation to skin and eyes.

Effects of Chronic Exposure: Solvents may cause defatting dermatitis.

LD 50 of Product:	N/E	LC 50 of Product:	N/E
-------------------	-----	-------------------	-----

Irritancy of Product:	Irritant to eyes and skin	Exposure Limits of Product:	N/E
-----------------------	---------------------------	-----------------------------	-----

Sensitization of Product:	Presently Unknown	Toxicologically Synergistic Materials:	N/E
---------------------------	-------------------	--	-----

--CARCINOGENICITY --REPRODUCTIVE EFFECTS --TERATOGENICITY --MUTAGENICITY

No information available

**SECTION VII-PREVENTIVE MEASURES**

Personal Protective Equipment to be used:

Gloves(specify):	Wear chemical resistant gloves	Eye (specify):	Safety Glasses
Respiratory(specify):	NIOSH Organic vapor mask	Clothing:	Not required
Respiratory Protection:	If used indoors or on a continuous basis, use of NIOSH approved cartridge type respirator is recommended		
Engineering Controls:	Ventilation - Local (Mechanical if used indoors on continuous basis)		
Leak and Spill Procedure:	Remove all sources of ignition. Use inert absorbent material, and non-sparking tools. Avoid breathing fumes. Ventilate area. Prevent from entering a watercourse.		
Waste Disposal:	Do not Puncture or incinerate containers even when empty. Dispose of in accordance with local, provincial and federal regulations. Aerosol cans to be disposed of at local recycling depots.		
Storage Requirements:	Store in a cool, well ventilated area not to exceed 50°C		
NPFA30B/CNFC 3.3.5	Level 2		
Handling Procedures and	Keep away from heat, sparks and open flames. Keep away from children. Donot inhale or ingest.		
TDG Classification:	Consumer Commodity		
WHMIS Classification:	A, B5, D1B, D2A, D2B	Complies with CCCR 2001	

**SECTION VIII-FIRST AID MEASURES**

Eye:	Flush immediately with plenty of water for at least 15 minutes and get immediate medical attention.
Skin:	Wash thoroughly with soap and water. If irritation and rash persists seek medical attention.
Inhalation	Remove to fresh air. Restore breathing if required. Seek immediate medical attention if discomfort persist.
Ingestion:	DO NOT INDUCE VOMITING. Get immediate medical attention.

**SECTION IX-PREPARATION DATE OF M.S.D.S.**

Additional Info/Comments:	Source Used: Supplier's data
Phone Number:	(905) 793-4311 Prepared By: Quality Control Laboratory
Date prepared:	January 26, 2012 Kleen-Flo Tumbler Industries Limited

**THIS SHEET SUPERSEDES ANY OTHER M.S.D.S. PREVIOUSLY PREPARED**